#### (19) World Intellectual Property Organization

International Bureau



## 

## (43) International Publication Date 10 February 2005 (10.02.2005)

**PCT** 

# (10) International Publication Number WO 2005/013435 A1

(51) International Patent Classification<sup>7</sup>: B60R 16/02

H01R 24/00,

(21) International Application Number:

PCT/CA2004/001425

(22) International Filing Date:

30 July 2004 (30.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/491,552

1 August 2003 (01.08.2003) US


- (71) Applicant (for all designated States except US): INTER AUTOMOTIVE CLOSURES INC. [CA/CA]; 521 Newpark Boulevard, Newmarket, Ontario L3Y 4X7 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ABBASOV, Askar [UZ/US]; 31020 Floralview Drive, Apartment 14-204, Farmington Hills, MI 48331 (US). STACEY, Donald,

Nicholas [US/US]; 6890 Renshaw, West Bloomfield, MI 48323 (US).

- (74) Agents: IMAI, Jeffrey, T. et al.; Magna International Inc., 337 Magna Drive, Aurora, Ontario L4G 7K1 (CA).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: SELF-ADJUSTABLE JUNCTION CONNECTOR SYSTEM



(57) Abstract: An electrical connector comprising a male housing and a female housing and electrical contacts extending therebetween when the male housing is plugged into the female housing. A shroud is reciprocatingly mounted to the male housing. When the shroud is in a retracted position, the electrical contact of the male housing is exposed to permit electrical contact with the female housing, and when the shroud is in an extended position it substantially covers the electrical contact of the male housing.

### WO 2005/013435 A1

| 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888 | 1888

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

#### Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments